

SPECIFICATIONS - ROOFING

	BMT	MASS	COVER WIDTH	RIB DEPTH	ROOF PITCH MINIMUM	Maximum recommended spacing of supports				
						ROOFS			EAVES OVERHANG	
						Single	End	Internal	Unstiffened	Stiffened
	mm	kg/m ²	mm	mm	Degrees	mm	mm	mm	mm	mm
CUSTOM ORB®	0.42	4.23	762	16	5	700	900	1200	200	300
	0.48	4.81	762	16	5	800	1300	1700	250	350

COMPATIBILITY OF DIRECT CONTACT BETWEEN METALS OR ALLOYS

ROOF DRAINAGE SYSTEM COMPONENTS & ANY CLADDING MATERIAL	ACCESSORIES OR FASTENER OR (UPPER SURFACE)		
	ZINCALUME®	COLORBOND® COLORBOND® ULTRA COLORBOND® METALLIC	COLORBOND® STAINLESS
ZINCALUME®	YES	YES	NO
COLORBOND® COLORBOND® ULTRA COLORBOND® METALLIC	YES	YES	NO
COLORBOND® STAINLESS	NO	NO	YES

ACCEPTABILITY OF DRAINAGE FROM AN UPPER SURFACE TO A LOWER METAL SURFACE

LOWER ROOF DRAINAGE SYSTEM MATERIAL	ACCESSORIES OR FASTENER OR (UPPER SURFACE)		
	ZINCALUME®	COLORBOND® COLORBOND® ULTRA COLORBOND® METALLIC	COLORBOND® STAINLESS
ZINCALUME®	YES	YES	YES
COLORBOND® COLORBOND® ULTRA COLORBOND® METALLIC	YES	YES	YES
COLORBOND® STAINLESS	YES	YES	YES